



Since 1980, PROTECH has been designing, manufacturing, and marketing Perimeter Intrusion Detection Systems (PIDS) to protect personnel, property, and assets at sensitive sites. We manufacture systems that give early warning of potential threats at the perimeter. PROTECH offers a complete range of perimeter intrusion detection systems and technologies including – G-FENCE fence-mounted intrusion detection, infrared beam technology (invisible fences), PIRAMID dual technology motions sensors and video analytic object detection and tracking. Our technology can be integrated with monitoring applications including Protech’s MAXIBUS, Smart Bridge, or Spectra

For additional information, contact:

PROTECH/Protection Technologies, Inc.  
529 Vista Blvd.  
Sparks, NV 89434

Phone: +1 775 856-7333 | Fax: +1 775 856-7658  
protechsales@protechusa.com  
www.protechusa.com

## ACTIVE INFRARED BARRIER

### DIVISION 28 – ELECTRONIC SAFETY AND SECURITY

#### MasterFormat 2020

**28 31 21 Area and Perimeter Intrusion Detection**

**28 31 21.17 Fixed Optical Beam Area and Perimeter Security Systems**

#### Notes to Specifier:

1. Where several alternative parameters or specifications exist, or where, the specifier has the option of inserting text, such choices are presented in **<bold text>**, where the parameter specified in [brackets] is the normal default.
2. Explanatory notes and comments are presented in *italic* text.

## ACTIVE INFRARED BARRIER

### PART 1 GENERAL

#### 1.01 SUMMARY

- A. Section includes an active infrared barrier system.
- B. Product - A system consisting of sensing towers which integrate transmitter and receiver functions in a single tower and create an infrared intrusion barrier and sends alarms through dry contact output.
- C. Related Requirements
  - 1. 28 01 30 Operation and Maintenance of Security Detection, Alarm and Monitoring
  - 2. 28 06 30 Schedules for Security Detection, Alarm and Monitoring
  - 3. 28 31 31 Intrusion Detection Interfaces

#### 1.02 REFERENCES

- A. Definitions
  - 1. Single face – Infrared beam transmission or reception, or both, from one surface (face) of a sensing tower.
  - 2. Double face – Infrared beam transmission or reception, or both, from opposing surfaces (faces) of a sensing tower.
  - 3. Cell – A mono directional Infrared transmitter-receiver device installed in a tower. A pair of cells, installed in 2 different towers, will create an Infrared detection beam between these towers.
- B. Reference Standards
  - 1. Electromagnetic compatibility
    - a. EU EMC Directives EN 55022, EN 55024
    - a. FCC-47 CFR Part 15, Class B

#### 1.03 SUBMITTALS

- A. Product Data
  - 1. Manufacturer's printed or electronic data sheets
  - 2. Manufacturer's installation and operation manuals
- B. Shop Drawings
  - 1. Termination points and enclosures

**1.04 QUALIFICATIONS**

- A. Manufacturer of system shall have a minimum of five (5) years' experience in the design, manufacture, and successful implementation of perimeter sensing systems.

**1.05 DELIVERY, STORAGE, AND HANDLING**

- A. Deliver the equipment system in the manufacturer's original, unopened, undamaged container with identification labels intact.
  - 1. Ship and store the system protected from mechanical and environmental conditions as designated by the Manufacturer.

**1.06 WARRANTY**

- A. The Manufacturer shall provide a limited warranty for the system to be free of defects in workmanship and material under normal operating conditions for a period of two years from the date of product shipment.

- END OF SECTION -

## **PART 2 PRODUCT**

### **2.01 EQUIPMENT**

- A. Manufacturer: PROTECH/Protection Technologies, Inc.  
529 Vista Blvd.  
Sparks, NV 89434  
Phone: +1 775 856-7333 | Fax: +1 775 856-7658  
protechsales@protechusa.com  
[www.protechusa.com](http://www.protechusa.com)
- B. Model: MIRIS 3100
- C. Alternates: None

### **2.02 GENERAL DESCRIPTION**

- A. The system shall detect all attempts at intrusion by using adjustable infrared barriers formed by two or more externally powered sensing towers, each of which communicates alarm information via relay outputs for each beam direction.
- B. Intrusion detection shall be based upon the interruption of pulsed infrared beams between sensing towers, spaced with a maximum range of 328 feet (100 m).

### **2.03 SYSTEM COMPONENTS AND OPERATION**

- A. Sensing towers shall be configurable for height and number of infrared beams.
1. Sensing towers shall be available for infrared beam operation in both single face and double face operation.
  2. Sensing towers shall be available configured as infrared transmitters, infrared receivers, or both.
  3. The response time for an intrusion alarm shall be selectable from 40 ms to 500 ms.
- B. The system shall operate with sensing towers spaced up to 100 m (328 feet)
- C. Alarm outputs per tower: Intrusion, disqualification, tamper
- D. Alarm indicator: Buzzer and LED in each tower
- E. Each sensing tower shall have an integrated anti-climbing cap.
- F. Each sensing tower shall have integrated alignment tools.
- G. The sensing tower shall be capable of in-line, corner, floor, or wall mounting.
- H. Each tower shall have an active heater set to deactivate at 95° F (35° C)

**2.04 DETAILED SPECIFICATIONS**

1. Number of tower faces: 1 or 2  
*See above note in 2.03 A 1.*
2. Number of cells per tower face: 4, 6, or 8 available
3. Effective beam angle: Horizontal +/- 90°, vertical +/- 10°
4. Beam Wavelength: 950 nm
5. # Channels (frequencies): 4 (1 channel per barrier)
  - a. Maximum range: 328 feet (100 m)
6. Power: **[24/48 VDC] <12 VDC>**  
*A 110 VAC power supply is optional.*  
*A 12 VDC 1.2 AH battery is optional.*
7. Physical
  - a. Tower height: **<6 ft. (2m) > <10 ft. (3m)>**

*The following table provides the available tower options:*

<i>Part no.</i>	<i>Height</i>	<i>Faces</i>	<i># Beams per Face</i>
<i>Tower 2MSF</i>	<i>6ft. (2 m)</i>	<i>1</i>	<i>4-6</i>
<i>Tower 2MDF</i>	<i>6ft. (2 m)</i>	<i>2</i>	<i>4-6</i>
<i>Tower 3MSF</i>	<i>10 ft. (3 m)</i>	<i>1</i>	<i>6-8</i>
<i>Tower 3MDF</i>	<i>10 ft. (3 m)</i>	<i>2</i>	<i>6-8</i>

- b. Mounting: **[floor sockets] < wall mounts>**
  - c. Cabling protection: Internal
  - d. Environmental
    - 1) Operating temperature: From -40°F to +158°F (-40°C and +70°C)
8. Alarms
  - a. Outputs: Dry contact relays
  - b. Parameters: Intrusion, disqualification, tamper

- END OF SECTION -

### **PART 3 EXECUTION**

#### **3.01 INSTALLERS**

- A. The Contractor's installers and technicians shall be factory trained and certified to install, service, and maintain the system.
- B. Contractor personnel shall comply with all applicable state and local licensing requirements.

#### **3.02 PREPARATION**

- A. Contractor shall insure that all products to be installed have been verified to possess the latest version of available firmware.

#### **3.03 INSTALLATION**

- A. The Contractor shall adhere to all Manufacturer's published installation procedures, diagrams, and guidance.
- B. Sensing Towers
  - 1. All vegetation shall be cleared from the sight path between adjacent sensing towers.

- END OF SECTION -